

Mira Select Flex Mixer Shower

Product Overview

The Mira Select Flex mixer shower is stylish and safety conscious with thermostatic temperature control.

Cool touch technology prevents the valve becoming hot during use. Featuring easy use levers and easy glide showerhead with extra long slide bar and hose. Ideal for small spaces as riser rail can be mounted in a corner.

Features & Benefits

- + Thermostatic control plus TMV3 approval for safe showering
- + Separate flow & temperature controls with extended lever controls
- + Maximum temperature stop
- + Cool Touch technology reduces the surface temperature when in use
- + 2m hose and 1m easy glide riser rail
- + Variable pipe inlet centres for easy installation, can be corner mounted
- + Inlet connections - 15mm compression, Outlet connection - ½" BSP flat face
- + Maximum static pressure 10.0 bar
- + Maximum maintained pressure 5.0 bar
- + Factory preset temperature at 41°C
- + Thermostatic shutdown within 2 seconds
- + Minimum maintained pressure (gravity system) 0.1 bar



Mira Select Flex Mixer Shower



Mira Select Flex Mixer Shower Valve

Warranty & Approvals



Mira Select Flex Mixer Shower

Product Specification

Water entry points	Rising, falling or rear
Inlet connections	15mm compression
Outlet connections	½" BSP male flat face or 15mm compression
Min maintained pressure	0.1 bar (1 metre head)
Max maintained pressure	5.0 bar (50 metre head)
Max static pressure	10.0 bar (100 metre head)
Flow rate (at handset)	9 l/min @ 0.5 bar
Temperature stability	+/- 2°C
Automatic shutdown	Within 2 secs
Factory set max temperature	41°C

Product Code

Mira Select Flex Mixer Shower

006MS10
